

50 Hz

3-Phase

Power Factor
Cos Φ = 0.8

Emissions
EU Stage IIIA Certified

Key Features

- Efficient water cooled Mitsubishi diesel engine
- EU Stage 3A emissions certified engine
- Heavy duty rubber captive anti-vibration mountings
- Single bearing CGT Stamford alternator
- Mechanical speed governor
- Three way fuel valve - single lever operation
- Integral 125 litre bunded fuel tank with filler cap and gauge
- Heavy duty zinc-treated central lift canopy c/w fork pockets
- Large door access for ease of maintenance
- Integral Industrial silencer
- DSE7320 MKII Deep sea Auto-start controller
- 4 pole Main line circuit breaker
- Heavy duty sealed lead acid battery 12v
- Lockable Battery isolator



Overall Dimensions & Weights Canopy Set

Length (L) = 2265mm Width (W) = 950mm
Height (H) = 1567mm

Dry Weight (inc oil) = 1120kgs
Operating Weight = 1275kgs

50HZ	Typical Sound Pressure Level at 75% of Prime Power dBA			
	1m	5m	7m	10m
dBA	72	64	62	58

Definition of Ratings & Reference Conditions

Prime Power (PRP) is the nominal output continuously available, where the average load (variable) does not exceed 70% of the prime power rating. 10% overload is available for a maximum of 1 hour in 12 hours of operation.

Standby Power (ESP) is the maximum output available, for up to 500 hours per year, where the average load (variable) does not exceed 70% of the standby power rating. No overload is available.

Standard Reference Conditions: air temperature 25°C (77°F), barometric pressure 100kPa, [110m (361ft) altitude], 30% relative humidity.

Note: The above ratings may be subject to derate at different operating conditions. Please see the Derate Guidelines on the JCB Broadcrown Website.

All power ratings and reference conditions in accordance with ISO 8528-1 and ISO 3046-1.

	Prime	Standby
Fuel Consumption at 100% Power l/h	10.3	11.6
Fuel Consumption at 75% Power l/h	8.0	9.0
Fuel Consumption at 50% Power l/h	5.7	6.4
Total Fuel Flow l/h	30	
Standard Fuel Tank	125	

50Hz RATINGS	PRIME POWER (PRP)		STANDBY POWER (ESP)		
Voltage	kVA	kWe	kVA	kWe	Amps
440/254	40	32	44	35	58
415/240	40	32	44	35	61
400/230	40	32	44	35	64
380/220	40	32	44	35	67